



- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. RATING: AC 125V 7A, AC 250V 4A
 5. CONTACT RESISTANCE: 20m ohm max. at 5V DC 1A.
 6. DIELECTRIC STRENGTH: AC 1500V RMS
 7. LIFE EXPECTANCY: Electrical: 6,000 cycle
 8. OPERATING FORCE: 550±150gf
 9. TRAVEL: Full: 5.5mm
 10. 2002/95/EC (ROHS) COMPLIANT

| | | | | |
|------|---------|-------------------------|---------|------|
| B | 16925 | FIXED NOTE 9 | 1/25/07 | TN |
| A | 10433 | RELEASED FOR PRODUCTION | | |
| REV. | ECN No. | DESCRIPTION | DATE | CHKD |

| | | | | | | |
|-------------|--|-------|---------|----|---------|-----|
| TITLE | | SCALE | DATE | DR | DWG | REV |
| P2270A2B18A | | 1.5:1 | 1/25/07 | TN | P030105 | B |



THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED