



- Material**
- Ⓐ Terminal body(metal housing of double): Brass(CuZn),NI plated
 - Ⓑ Terminal body(metal housing of single): Brass(CuZn),NI plated
 - Ⓒ Terminal screw: Steel Zinc plating "-" slot type
 - Ⓓ Wire guard(short): Stainless steel
 - Ⓔ Insulator(lever): Thermoplastic (UL94V-0)
 - Ⓕ Insulator(housing): Thermoplastic (UL94V-0)
 - Ⓖ Wire guard(long): Stainless steel

Electrical cULus VDE
 Voltage rating: 400VAC / 450VAC
 Current rating: 10A / 24A
 Wire range: 0.34-2.5mm²
 Solid wire(AWG): 14-22
 Stranded wire(AWG):14-22
 Torque(Lb-In): 3.5 / 0.5
 Screw: M3
 Wire strip length: 7-8mm
 Withstanding Voltage: 1.8KV/2.5KV
 Operating temperature: -40°C to +115°C
 Safety Approval:

RoHS compliant
 Unit: mm

 File No.: E349947

Scale	Free
TOLERANCE	
X.	±0.50
X.X	±0.30
X.XX	±0.10
DIM	TOL
X.°	±1°
Angle	TOL

		Id.	Modification	Date	Name
Ⓐ	Update to new drawing and add UL			15.03.2016	Amy
Ⓞ	Updating			19.04.2010	Alex

	Date	Name
Drawn	19.04.2010	Alex
Approved	15.03.2016	Amy

ASSMANN
 wsw components

Customer-No.	ASSMANN WSW-No.	Drawing-No.
	A-TB100-TM04	ASS 2011A CO
		rev01

Replace
 Sheet