

## Specification Sheet

Part Number: MBT33S-S



Stainless Steel Tie, 33" Long, 202lb Tensile Strength, SS304, Metal, 50/pkg

Article Number	111-93338
Type	MBT33SS
Color	Metal (ML)
Features & Benefits	<ul style="list-style-type: none"><li>• 304 grade stainless steel offers excellent resistance to corrosion, weather and chemical resistance.</li><li>• Ball bearing locking mechanism assures high tensile strength and easy insertion.</li></ul>
Quantity Per	bag
Product Description	HellermannTyton's stainless steel ties are designed with a ball bearing locking mechanism to assure high tensile strength and easy insertion when securing hoses, cables, pipes and more. Available in 304 or 316 grades of stainless steel, providing protection when used in corrosive environments, fire resistance and temperature extremes.
Short Description	Stainless Steel Tie, 33" Long, 202lb Tensile Strength, SS304, Metal, 50/pkg

Global Part Name

MBT33SS-SS304-ML

Minimum Tensile Strength (Imperial)

202.0

Minimum Tensile Strength (Metric)

900.0

Length L (Imperial)

33.0

Length L (Metric)

838.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

ball bearing lock

Variant

No Serration

Width W (Imperial)

0.18

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.67

Bundle Diameter Min (Metric)

17.0

Bundle Diameter Max (Imperial)

10.0

Bundle Diameter Max (Metric)

254.0

Thickness T (Imperial)

0.01

Thickness T (Metric)

0.3

<b>Material</b>	Stainless Steel (SS304)
<b>Material Shortcut</b>	SS304
<b>Flammability</b>	Non-Burning
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-112°F to +1000°F (-80°C to +538°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	7326908595
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	8.62

