

Specification Sheet

Part Number: 170-03142



Braided Sleeving, Split Wrap, Flame Retardant, .5" Dia, PET, Black, 150 ft/bulk reel

Article Number

170-03142

Type

BSSWFR120B

Color

Black (BK)

Features & Benefits

- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
- Unique construction retains shape and rigidity throughout unrolling.
- Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

Quantity Per

reel

Product Description

A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

Short Description

Braided Sleeving, Split Wrap, Flame Retardant, .5" Dia, PET, Black, 150 ft/bulk reel

Global Part Name

BSSWFR120B-PET-BK

Length L (Imperial)

150.0

Length L (Metric)

45.7

Bundle Diameter Min (Imperial)

0.5

Bundle Diameter Min (Metric)

12.7

Bundle Diameter Max (Imperial)

0.02

Bundle Diameter Max (Metric)

0.5

Diameter D (imperial)

0.50

Diameter D (metric)

12.7

Nominal Diameter (Imperial)

1/2

Nominal Diameter (Metric)

12.7

Wall Thickness WT (Imperial)

0.025

Wall Thickness WT (Metric)

0.64

Material

Polyester (PET)

Material Shortcut

PET

Flammability

FAR 25 UL VW-1

Halogen free

Yes

Operating Temperature (Metric)

-94°F to +257°F (-70°C to +120°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

UL Recognized (US)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

150

Package Quantity (Metric)

45.72

Customs Number

3926909987

Weight (Metric)

0.95

Weight (Imperial)

2.1