

Specification Sheet

Part Number: TAG68L-789

HellermannTyton Laser Tag Label, 3.8" x .275", 70 Per sheet, PET, White, 2500/pkg

Article Number	594-68789
Type	TAG68L
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none">•Laser printable white polyester has a smooth surface, allowing for the highest resolution and print contrast.•The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.•Lasertags are not affected by the high heat required in a laser printer.
Quantity Per	pack
Product Description	<p>HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 789 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking.</p>

Short Description

Laser Tag Label, 3.8" x .275", 70 Per sheet, PET, White, 2500/pkg

Global Part Name

TAG68L-789-WH

Width W (Imperial)

3.8

Width W (Metric)

96.5

Bundle Diameter Min (Imperial)

.15

Bundle Diameter Min (Metric)

3.80

Thickness T (Metric)

64.0

Height H (Imperial)

0.275

Height H (Metric)

6.98

Material

Type 789, Polyester (PET)

Material Shortcut

789

Adhesive

Acrylic

Halogen free

No

Adhesive Operating Temperature

-40°F to +302°F (-40°C to +150°C)

Operating Temperature (Metric)

-40°F to +300°F (-40°C to +149°C)

Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	2500
Package Quantity (Metric)	2500
Customs Number	3919905060
Labels per Column	35
Labels per Row	2
Weight (Metric)	0.521
Weight (Imperial)	1.14