

**Article Number**

148-90000

Type

HECP-2

Color

Yellow (YE) Clear (CL)

Features & Benefits

- Double Spring Technology for safe, secure and reliable connections
- Low Insertion Forces + High Retention Values
- Accommodates both solid and stranded wire cores
- Polycarbonate Housing for quick visual inspection; Meets UL 92V2 standards
- Low insertion forces reduces buckling of stranded wire
- Able to combine solid and stranded within same housing
- Separate test port for fast, easy confirmation of connection
- Quick Fit Insertion relieves installer in difficult spots like overhead installations, eliminates twisting motion and reduces overall assembly and connection time.
- Max Current Rating to 24 A
- Max Voltage Rating to 600 V (c UL us)

Quantity Per

box

Product Description

Helacon Plus is a unique push-in wire connector with double spring technology. Double spring design requires less insertion force and delivers superior retention values. Helps alleviate repetitive motion injuries often associated with twist-on style connectors.

Short Description

HelaCon Plus Push-In Style Wire Connector, Double Spring, 2-Port, Polycarbonate, Yellow, 100/pkg

Global Part Name

HECP-2-PC-CL/YE

Port Count

2

Length L (Metric)

19.0mm

Width W (Imperial)

0.46"

Width W (Metric)

11.75mm

Height H (Imperial)

0.41"

Height H (Metric)

10.45mm

Material

Polycarbonate (PC)

Material Shortcut

PC

Flammability

UL 94 V2

Halogenfree

Yes

Operating Temperature Metric

-22°F to +185°F (-30°C to +85°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Certification/Specification WEB

VDE | DIN EN 60998-2-2:2005-03 SEMKO KEMA-KEUR | EN 60998-2-2:1993
ENEC UL | ANSI/UL 486-B UL | ANSI/UL 486-A UL | ANSI/UL 486-C DEMKO
CEN FIMKO NEMKO

ULListed (US and Canada)

Yes

Package Quantity(Imperial)

100

Package Quantity (Metric)

100

Customs Number

3926909987

Content Unit(BMEcat)

pieces

Weight (Metric)

0.275kg

Weight (Imperial)

10.2 lbs