


LOCKING SERRATIONS PREVENT
LOOSE CONNECTIONS CAUSED
BY VIBRATION.

- NOTES:
1. CONDUCTOR MAT'L: COPPER
PLATING: TIN
 2. PVC INSULATION: COLOR CODED
SEE CHART

MULTI-STUD HOLE SIZE
SEE CHART



STUD HOLE SIZES:	
06	= .146
08	= .173
10	= .198

PART NUMBERS ARE FOR LOOSE PIECE TO ORDER PARTS ON TAPE ADD A "T" TO END OF PART NUMBER

PART NUMBER	WIRE RANGE AWG	INSUL. COLOR	"L" MAX.	"W" MAX.	"C" MIN.	"C" MAX.	"D" MIN.			STUD SIZE RANGE FOR EA. PART No.	STOCK THICKNESS
A-1006-MS	22-18	RED	.866	.348	.330	.447	.062			6 , 8 , 10	.028
B-1006-MS	16-14	BLUE	.866	.362	.330	.447	.081			6 , 8 , 10	.031
C-1006-MS	12-10	YELLOW	.890	.410	.330	.447	.128			6 , 8 , 10	.040

REVISE ONLY ON CAD SYSTEM

TITLE
KRIMPTITE
MULTI-STUD
RING TONGUE TERMINAL

**CUSTOMER
DRAWING**

DRWG. BY EMF
CHK'D. BY
APP'D. BY
SCALE NO:NE

molex ETC INC.
PINELLAS PARK, FLA. 34665 U.S.A.
PART NO. SEE TABLE
FILE NAME MSRINGKR CST

SHEET NO.
DATE 08/09/93
DRWG. NO. CUSTOMER DWG.
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX-ETC INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.
DIV. SIZE A