

THE CRIMP DIM'S APPLY ONLY TO THE ABOVE COMBINATIONS.

METHOD OF GAGING CRIMP DIMENSIONS.

SUPERSEDED BY I.S. 2496


| | | | | |
|---|---|------------|---------------------|----|
| 2 | - | 1-21046-3 | RETAINING RING | 13 |
| 1 | B | 306205-3 | INDENTER-INSULATION | 12 |
| 1 | A | 5305832-5 | SPACER | 11 |
| 1 | B | 1-306542-5 | INDENTER-BRAID | 10 |
| 1 | A | 5305832-4 | SPACER | 9 |
| 1 | B | 306207-2 | BARREL-INSERT-LOWER | 8 |
| 1 | B | 306208-2 | BARREL-INSERT-UPPER | 7 |
| 1 | A | 5305832-3 | SPACER-SPECIAL | 6 |
| 1 | B | 1-306541-5 | ANVIL-BRAID | 5 |
| 1 | A | 1-306113-3 | EJECTOR | 4 |
| 1 | B | 306206-3 | ANVIL-INSULATION | 3 |
| 2 | A | 306105-7 | SCREW-SPECIAL | 2 |
| | | | | 1 |

DIMENSIONS IN INCHES DO NOT SCALE PRINT.

PRINTED 18

| LTR | REVISION RECORD | DR | CHK | DATE |
|-----|------------------|-----|-----|------|
| C | SUB BY I.S. 2496 | EIF | EIF | 8/77 |
| B | REVISED | RS | | 8/79 |
| A | REVISED | BS | | 2-80 |

| | |
|-----------------|-----------------------|
| NUMBER 69408 | REQUIRED PER ASSEMBLY |
| | DESCRIPTION |

| | | | | |
|--|---------------------------|-------|--|---------|
| DWG SIZE | NUMBER | NAME | REMARKS | ITEM NO |
| | | | | |
| ©1964 BY AMP INCORPORATED. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING. | | | CUSTOMER COPY REFERENCE ONLY | |
| DR | MATERIAL AND FINISH | |  AMP INCORPORATED HARRISBURG, PENNA. | |
| CHK | CLASS | | CLASS <u>H</u> | |
| DE | WIRE - RANGE - INSULATION | TYPE | TYPE <u>BNC-COAX.</u> | |
| APP | TOLERANCE EXCEPT AS NOTED | SCALE | LOC | NO |
| | ± .015 ± 1° 0' | 4-1 | M | B 69408 |
| | NAME <u>DIE ASS'Y</u> | | | |