	T G	m	D C B A	_
4	R 22.6 Max W D D D D D D D D D D D D D D D D D D	S C C C C C C C C C C C C C C C C C C C	Image: Note of the second se	4
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Keying Shown as example Connector dimension Dim Nominal		
2	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8µm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories	A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed PN: 8D711F04AC	2
	-Derivered with Souhad Contacts and Accessones -Temperature Range : -65°C to +200°C -Salt Spray : 48 hours -Mass : 17.99 g ± 10%		A 30-09-2016 First Release MOD N° ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Receptacle 8D series	
<u> </u>	BASIC SERIES: 8D 7 - 11 F 04 SHELL TYPE : Jam nut Receptacle	A C ORIENTATION : C CONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 11-04	SCALE General linear NPRDS / PROJECT NA Image: Tolerances: 859 SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU FORMAT SOURIAU DRG N° SHEET A3 8D711F04AC-C 1/2	1
L	H G I	F E	A B A	

Г	I G	т			
4	$\underbrace{\text{Contact Layout}}_{-,4} \qquad \qquad$		Panel cutout JAM NUT RECEPTACLE (TYPE 7)		4
	$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$		Dim Nomi	nal	
ω			B 19.59+0 ØC 20.96+0	/-0.25	3
			due to a use of the the Specifications issued	iable for any non-conformity or damage Products which does not comply with by either of the Parties or by a third party commendation, technical notice.) Country Jurisdiction & Control List	
N			A 30-09-2016 First Release	FR Not Listed 3D711F04AC Image: Control List	2
			ISS DATE Latest modification - by		MOD N°
			Designed By: Date:	CUSTOMER DRAWING	
			TITLE AI	uminium Receptacle 8D series	
<u> </u>				heral linear NPRDS / PROJECT ilerances: 859 ± This document is the proper SOURIAU SOURIAU	-ty of
				JRIAU.COM it must not be reproduced communicated without perm	
				URIAU DRG N° D711F04AC-C	SHEET 2/2
L	H G I	FE		B A	<i>.</i>