

Specification Sheet

Part Number: 157-00035



Wide Strap Cable Tie with 8mm Stud Mount, 12.7" Long, .5" Wide, PA66HIRHSUV, Black, 300/Bag

Article Number	157-00035
Type	WSI8MM
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Mount provides low insertion and high extraction forces which makes for a strong and easy installation.• Clamping rails increase grip on round bundles.• Thinner strap provides increased flexibility for improved ergonomics.• Tie utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.
Quantity Per	bag

Product Description

Wide Strap Heavy Duty Cable Ties features a stud mount for direction application onto a 8 mm threaded stud. The tie is 0.5" wide, and handles bundles from 0.38" - 4.2". The low profile mount design engages a minimum of 4 threads on the stud which makes it easier to apply additional mounts onto one stud.

Short Description	Wide Strap Cable Tie with 8mm Stud Mount, 12.7" Long, .5" Wide, PA66HIRHSUV, Black, 300/Bag
Global Part Name	WSI8MM-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	120
Minimum Tensile Strength (Metric)	534
Length L (Imperial)	12.7
Length L (Metric)	322.6
Fixation Method	Weld Stud Fixing
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.5
Width W (Metric)	12.7
Bundle Diameter Min (Imperial)	0.38
Bundle Diameter Min (Metric)	9.5
Bundle Diameter Max (Imperial)	3.2

Bundle Diameter Max (Metric)

82.5

Stud Diameter (Metric)

M8

Stud Diameter (Imperial)

5/16

Material

Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut

PA66HIRHSUV

Flammability

UL 94 HB

Operating Temperature (Metric)

-40°F to +230°F (-40°C to +110°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

300

Package Quantity (Metric)

300

Customs Number

3926909987

Content Unit(BMEcat)

pcs.

