



CIRCUIT NO.

	50.8	47.5	20	
	48.3	45	19	
	45.8	42.5	18	
	43.3	40	17	
	40.8	37.5	16	
	38.3	35	15	
	35.8	32.5	14	
	33.3	30	13	
	30.8	27.5	12	
	28.3	25	11	
	25.8	22.5	10	
	23.3	20	9	
	21.4	20.8	17.5	8
	18.9	18.3	15	7
	16.4	15.8	12.5	6
	13.9	13.3	10	5
	11.4	10.8	7.5	4
	8.9	8.3	5	3
	6.4	5.8	2.5	2
DIM. C	DIM. B	DIM. A	NO. OF CKTS.	

角度 ANGLE		$\pm 30^\circ$						材料 MATERIAL	MOLEX-JAPAN CO.,LTD. 日本モレックス株式会社
30以上 OVER		± 0.3						66NYLON, UL94V-0	
10以上 OVER 30未滿 UNDER		± 0.25	A	REVISED (J20819)	H.H.	M.F.	92/11	仕上げ FINISH	REVISION RECORD
10未滿 UNDER		± 0.2	0	RELEASED (J20038)	K.T.	H.H.	92/11	適用電線範圍 WIRE RANGE	TITLE 名称
一般公差 GENERAL TOLERANCES			記号 LTR	変更内容 REVISION RECORD	DR. CHK.	日付 DATE		被覆外径 INS. RANGE	2.5 LOW PROFILE RECEPTACLE HOUSING (DYED COLOR)
								DRAWN BY 92/11 K.I.OJO	DWG. NO. SHEET 1 OF 2
								CHK'D BY 92/11 榎原 伸太郎	REV A
								APP'D BY 92/11 榎原 伸太郎	SD-5264-N-***
								尺度 SCALE 5 - 1	

DWG. NO. SHEET 2 OF 2
SD-5264-N-**-**

E

D

C
DIMENSIONS IN METRIC DO NOT SCALE DRAWING

B

A

F

E

D

C

B

A

NOTES

1. SUITABLE TERMINAL : 5263 SERIES
2. MATES WITH : 5267, 5268 SERIES
- △ 3 9 CIRCUITS OR MORE WITHOUT LOCK.
4. LEGEND

5264 - N - **

BASE NUMBER _____
 CIRCUIT SIZE _____
 DYED COLOR _____
 BL : BLACK
 BU : BLUE
 GR : GREEN
 RE : RED
 YE : YELLOW

39-02-6205	5264-20-YE	39-02-6204	5264-20-RE	39-02-6203	5264-20-GR	39-02-6202	5264-20-BU	39-02-6201	5264-20-BL	20
▲ -6195	▲ -19-YE	▲ -6194	▲ -19-RE	▲ -6193	▲ -19-GR	▲ -6192	▲ -19-BU	▲ -6191	▲ -19-BL	19
-6185	-18-YE	-6184	-18-RE	-6183	-18-GR	-6182	-18-BU	-6181	-18-BL	18
-6175	-17-YE	-6174	-17-RE	-6173	-17-GR	-6172	-17-BU	-6171	-17-BL	17
-6165	-16-YE	-6164	-16-RE	-6163	-16-GR	-6162	-16-BU	-6161	-16-BL	16
-6155	-15-YE	-6154	-15-RE	-6153	-15-GR	-6152	-15-BU	-6151	-15-BL	15
-6145	-14-YE	-6144	-14-RE	-6143	-14-GR	-6142	-14-BU	-6141	-14-BL	14
-6135	-13-YE	-6134	-13-RE	-6133	-13-GR	-6132	-13-BU	-6131	-13-BL	13
-6125	-12-YE	-6124	-12-RE	-6123	-12-GR	-6122	-12-BU	-6121	-12-BL	12
-6115	-11-YE	-6114	-11-RE	-6113	-11-GR	-6112	-11-BU	-6111	-11-BL	11
-6105	-10-YE	-6104	-10-RE	-6103	-10-GR	-6102	-10-BU	-6101	-10-BL	10
-6095	-09-YE	-6094	-09-RE	-6093	-09-GR	-6092	-09-BU	-6091	-09-BL	9
-6085	-08-YE	-6084	-08-RE	-6083	-08-GR	-6082	-08-BU	-6081	-08-BL	8
-6075	-07-YE	-6074	-07-RE	-6073	-07-GR	-6072	-07-BU	-6071	-07-BL	7
-6065	-06-YE	-6064	-06-RE	-6063	-06-GR	-6062	-06-BU	-6061	-06-BL	6
-6055	-05-YE	-6054	-05-RE	-6053	-05-GR	-6052	-05-BU	-6051	-05-BL	5
-6045	-04-YE	-6044	-04-RE	-6043	-04-GR	-6042	-04-BU	-6041	-04-BL	4
▼ -6035	▼ -03-YE	▼ -6034	▼ -03-RE	▼ -6033	▼ -03-GR	▼ -6032	▼ -03-BU	▼ -6031	▼ -03-BL	3
39-02-6025	5264-02-YE	39-02-6024	5264-02-RE	39-02-6023	5264-02-GR	39-02-6022	5264-02-BU	39-02-6021	5264-02-BL	2
EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	EDP NO.	ENG. NO.	NO. OF CKTS.
5264-N-YE		5264-N-RE		5264-N-GR		5264-N-BU		5264-N-BL		

材料 MATERIAL		66NYLON, UL94V-0		MOLEX-JAPAN CO.,LTD. 日本モレックス株式会社	
仕上げ FINISH		— —		REVISE ONLY ON CAD SYSTEM	
適用電線範囲 WIRE RANGE		— —		TITLE 名称 2.5 LOW PROFILE RECEPTACLE HOUSING (DYED COLOR)	
被覆外径 INS. RANGE		— —		DWG. NO. SHEET 2 OF 2 REV	
DRAWN BY 02/11 H.HIRAMOTO		CHK'D BY 02/11 H.HIRAMOTO		SD-5264-N-**-**	
APP'D BY 02/11 M.HIKOSHIMA		尺 度 SCALE 5 - 1		A	
DR. 日付 DATE		REVISION RECORD			
一般公差 GENERAL TOLERANCES		記号 LTR		変更内容	
30° 以上 OVER		+0.3		A SEE SHEET 1 OF 2	
10° 以上 30° 未満 UNDER		+0.25		SEE SHEET 1 OF 2	
10° 未満 UNDER		+0.2			

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX(JAPAN) AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
 本図面は日本モレックス(株)の所有する情報を含むもので 当社の許可なく複製を禁止する。
 EN-01C(032)MXJ-32

8

7

6

5

4

3

2

1