



- Notes
- 1 Applicable crimping contact: JRC-SC-112 (CL114-0241-8)
 - 2 Applicable crimp contact extraction tool: HR41A-TP (CL150-0405-7)
 - 3 Rotation examples are shown for Ref. No. ①, ③, ④ and ⑦.
 - ④ Fig. B-B shows the state applicable contact assembled and 3-step sequential structure. Contact No. ⊕ has functions as ground contact.
 - ⑤ Fig.1 shows the appearance after assembly.
 - 6 The cable pull and twisting strength and other characteristics may differ, depending on the cable structure, please confirm before the use.
 - 7 The assembly of this product applies to the manual ETAD-C0312.

4	PBT	(Black)UL94V-0					
3	PBT	(Black)UL94V-0	7	PBT	(Black)UL94V-0		
2	Silicone rubber	(Red)	6	Polyamide	(White)UL94V-0		
1	PBT	(Black)UL94V-0	5	Silicone rubber	(Red)		
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS		
UNITS	mm	SCALE	2 : 1	COUNT	1	DESCRIPTION OF REVISIONS	DESIGNED
						DIS-C-003748	MM. ISHII
							CHECKED
							EJ. KUNII
							DATE
							14. 11. 28
APPROVED : SU. OBARA			13. 06. 13		DRAWING NO.		
CHECED : HY. KOBAYASHI			13. 06. 13		EDC3-118140-00		
DESIGNED : HN. TANAKA			13. 06. 13		PART NO.		
DRAWN : HN. TANAKA			13. 06. 13		HR41A-17WBP-5SC		
					CODE NO.		
					CL141-0200-3-00		
					1/1		