



- NOTES:
1. HOUSING MATERIAL: ALUMINUM ALLOY A360-T6
 2. HANDLE MATERIAL: NYLON ZYTEL 101
 3. GLOBE MATERIAL: TEMPERED SODA LIME GLASS
 4. HOOK MATERIAL: #2024 ANNEALED ALUMINUM WIRE
 5. DRIVER ENCLOSURE: RUBBER
 6. cULus LISTED E30252
 7. HAZARDOUS LOCATIONS: CLASS I GROUP C & D, CLASS II GROUP F & G
 8. NEMA 4X
 9. TEMP RATING; T3B
 10. INPUT: 120-277VAC, .18A, 21 W
 11. LEDS: 5000K, 80CRI

CATALOG #	MATERIAL #	"A"
1655-12A	1301050082	25'
1655-12B	1301050083	50'
1655-12D		100'

RELEASE EC NO: IPG2015-2110 DRWN: PSNAGEL 2015/06/09 CHKD: HKNEELAN 2015/06/15 APPR: BWOODMAN2016/01/21	DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCH [MM]		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
		$\nabla=0$ $\sphericalangle=0$	mm	INCH	DRAWN BY PSNAGEL	DATE 2015/06/09	TITLE SALES DRAWING HI OUTPUT LO VOLT LED HAZ LOCATION HANDLAMP		
		4 PLACES ±---	±---	CHECKED BY HKNEELAN	DATE 2015/06/15				
		3 PLACES ±---	±.005	APPROVED BY BWOODMAN	DATE 2016/01/21				
	2 PLACES ±0.13	±.010	MATERIAL NO.		DOCUMENT NO. SD-1655-12	SHEET NO. 1 OF 1			
	1 PLACE ±0.25	±.020	SEE CHART						
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			ANGULAR ±.5°		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				