

Specification Sheet

Part Number: 170-03194



Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, .75" Dia, AL/GF, Silver, 15/box

Article Number

170-03194

Type

BSHTTSW34SB

Color

Silver (SR)

Features & Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Quantity Per

box

Product Description

Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance.

Short Description

Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, .75" Dia, AL/GF, Silver, 15/box

Global Part Name

BSHTTSW34SB-GF-AL-ML

Length L (Imperial)

4.0

Length L (Metric)

1.22

Bundle Diameter Min (Imperial)

0.1

Bundle Diameter Min (Metric)

2.54

Bundle Diameter Max (Imperial)

0.65

Bundle Diameter Max (Metric)

16.5

Diameter D (imperial)

0.75

Diameter D (metric)

19.05

Nominal Diameter (Imperial)

3/4

Nominal Diameter (Metric)

19.05

Wall Thickness WT (Imperial)

0.042

Wall Thickness WT (Metric)

1.06

Material

Glass fiber with aluminium foil (GF-AL)

Material Shortcut

GF-AL

Flammability

Non-Flammable

Halogen free

Yes

Operating Temperature (Metric)

-76°F to +491°F (-60°C to +255°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

15

Package Quantity (Metric)

15

Customs Number

7019901000