

Honeywell Sensing and Control

Search



SD3491-001
 (Home : Products : Sensors » Infrared Sensors » Phototransistors - Metal Package » SD3491)

narrow your search

Products

- Controls Monitoring and Lighting (352)
- Machine Safety (1727)
- Sensors (5898)
- Switches (9774)
- Wireless (39)

Technology

- Control and Instrumentation (1052)
- Electromechanical (9300)
- Microstructure (1491)
- Optical/Infrared (1042)
- Thick Film (1409)
- More...



SD3491 Series Silicon Phototransistor, TO-46 Metal, Flat Window Can

Actual product appearance may vary.

[Sales & Service](#)
[Distributor Inventory](#)

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site
 WGLA and WPMM
 XYR6000™

[find out more](#)

white papers

- Wireless Switches Offer Unlimited Benefit
- Basic Switches Are Not Created Equal
- Applying Precision Switches Sensors for Medical Devices
- New Ways to Measure Torque
- Choosing Safety Switches
- Specifying Hour Meters

Need help?

[Click here to contact us](#)

contacts

- Customer Service
- Technical Support
- Global Sales & Service
- View Site Demo
- Site Comments?

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.



Meet Dr. Larry

my links

- Login to iCOM
- Login to Rep/AD Portal
- Login to Digital University

News Center

HONEYWELL ANNOUNCES ADDITION TO RELIALIGN™ RESIDENTIAL DOOR INTERLOCK SWITCHES THAT FEATURE RUGGED, PLASTIC HOUSING

HONEYWELL RELEASES UNLIMITED POTENTIAL WITH NEW LIMITLESS™ WIRELESS SWITCHES

HONEYWELL'S XYR6000 WIRELESS POSITION SENSOR ENABLES MONITORING IN HAZARDOUS AREAS AND REMOTE LOCATIONS

MICRO SWITCH Anniversary site

[Overview](#) |
 [Specs](#) |
 [Documentation](#) |
 [Application Notes](#)

Product Specifications

Series Name	SD3491
Product Type	IR Component
Angular Response (Degree)	90
Light Current Minimum	0.45 mA
Package Type	T0-46, Flat Window
Hermetic Style	Yes
Rise and Fall Time	2 μs
Power Dissipation	250 mW
Operating Temperature	-65 °C to 125 °C [-85 °F to 257 °F]
Dark Current	100 nA
Collector-Emitter Breakdown Voltage	30 V
Emitter-Collector Breakdown Voltage	5 V
Collector-Emitter Saturation Voltage	0.4 V
Comment	The radiation source is a tungsten lamp operating at a color temperature of 2870°K.
Availability	Global