



20. 40. 60 POS
(1.27mm 塔載面側)
ON BOARD SIDE

30. 50 POS
(1.27mm 塔載面側)
ON BOARD SIDE

6-	20	9	11.43	17.40	19.20	
4	60	29	36.83	42.80	44.60	
6-	50	24	30.48	36.45	38.26	
2	40	19	24.13	30.10	31.90	
1	30	14	17.78	23.75	25.55	
5	20	9	11.43	17.40	19.20	
4	60	29	36.83	42.80	44.60	
3	50	24	30.48	36.45	38.26	
2	40	19	24.13	30.10	31.90	
1	30	14	17.78	23.75	25.55	
REMARK	PART NUMBER	POS	TL	A	B	D
	174216-1	30	14	17.78	23.75	25.55

- 注記
- 基板表面はレジスト処理を施すこと。
 - 基板の寸法はコネクタ塔載面側から示す。
 - 基板及びコネクタの数は「DATAM」位置から数える。
 - ハウジング材料：P.B.T 樹脂 (94V-0)。色：黒色
 - コネクタ材料：焼青銅
 - コネクタ表面は、1.27mm MIN 厚の全面ニッケル下地あり、其上に接触部分は 0.76mm 厚の 0.2mm MIN 厚の金あり、半田付部分は 1mm MIN 厚の半田あり。
- NOTE
- USE A P.C.B WHOSE ARE TREATED WITH SOLDER RESIST.
 - SHOW P.C.B LAYOUT FROM ON BOARD SURFACE SIDE.
 - NUMBER THE CONTACT IN THE P.C.B OR CONNECTOR CONSECUTIVELY FROM "DATAM" SIDE.
 - HOUSING MATERIAL: P.B.T (UL94V-0) / BLACK
 - CONTACT MATERIAL: PHO-BRONZE
 - FINISH: NICKEL 0.0017MM THK. OVERALL SELECTIVE GOLD 0.00076MM. OR 0.0002MM. ON CONTACT AREA AND TIN-LEAD 0.001MM THK. ON TUNE AREA.

E	REVISED	EQJ-1347	1/6.5	R	1/4
D	REDRAWN	W/ CHANGE	3-25	R	1/18
LTR	製	製 (REVISION RECORD)	DR	CHK	DATE

材料 (MATERIAL)	仕様 (SPECIFICATION)	公差 (TOLERANCE)	検査 (INSPECTION)
銅 (COPPER)	焼青銅 (BURNED BRASS)	±0.05	目視 (VISUAL)
樹脂 (RESIN)	P.B.T (UL94V-0)	±0.1	目視 (VISUAL)
金 (GOLD)	0.00076mm	±0.0001	目視 (VISUAL)
ニッケル (NICKEL)	0.0017mm	±0.0001	目視 (VISUAL)
半田 (SOLDER)	60Sn40Pb	±0.05	目視 (VISUAL)

A

B

C

D

PRINT DIST

単位: mm DIMENSIONS IN MM. DO NOT SCALE PRINT

AMP-J-030-2
REV. 9/83

(CUSTOMER DRAWING) 参考図面

AMP
ELECTRONIC COMPONENTS
TOKYO, JAPAN

CAP ASSY (VERTICAL / % SCREW HOLE)
AMPLIMITE 050 SERIES I B-7b-B COM

寸法 (DIMENSIONS)	公差 (TOLERANCE)	検査 (INSPECTION)
10.2 ±0.2	±0.05	目視 (VISUAL)
30.2 ±0.25	±0.1	目視 (VISUAL)
30.2 ±0.25	±0.1	目視 (VISUAL)
5 ±0.1	±0.05	目視 (VISUAL)

材料 (MATERIAL)	仕様 (SPECIFICATION)	公差 (TOLERANCE)	検査 (INSPECTION)
銅 (COPPER)	焼青銅 (BURNED BRASS)	±0.05	目視 (VISUAL)
樹脂 (RESIN)	P.B.T (UL94V-0)	±0.1	目視 (VISUAL)
金 (GOLD)	0.00076mm	±0.0001	目視 (VISUAL)
ニッケル (NICKEL)	0.0017mm	±0.0001	目視 (VISUAL)
半田 (SOLDER)	60Sn40Pb	±0.05	目視 (VISUAL)