

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION OCT., 2016.
 © COPYRIGHT 2016 By Tyco Electronics Japan G.K. ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
D4	REVISED	ECR-16-003344	24OCT2016	KF	HY

Top view dimensions: 29.7, 18.5, 4.5, 6.4, 3.2, 56.

Side view dimensions: 45, 18.5, 4.5, 6.4, 3.2.

Dimensions: 15, 11.8, 5.2, 1, 5.2, 1.85, 6.25, 49.9, 18, 42, 2.3, 0, 3.5, 6.6, 9.1, 14.6, 17.1, 19.6, 22.1, 24.6, 27.6, 30.1, 32.6, 35.1, 37.6.

< MOUNTING DIMENSIONS FOR P. C. BOARD; TOLERANCE ±0.1 >
 プリント基板取付寸法図
 一般公差: ±0.1
 (公差は累積しないこと)

Dimensions: 26xØ1.1, 6.25, 2xØ3.5, 49.9, 4.5, 9.6, 15 MAX.

△ MUST BE KEPT BETWEEN [X] AND 2
 2. THE MATING PLUG HSG.PART NUMBER: 178747, 917850
 3. RECOMMENDED MOUNTING SCREW; 3mm DIA, 6mm LENGTH (MAX.)
 PAN HEAD, CLASS 2 TAPPING SCREW SPECIFIED IN JIS B1115, B1122
 (TIGHTENING TORQUE; 0.4N-m (4Kg-cm) MAX)
 △ CIRCUT NUMBER
 POWER CIRCUIT NO. (23) ~ (26)
 SIGNAL CIRCUIT NO. (1) ~ (22)
 △ INDICATED PREFIX AND ID MARK OF PRODUCT P/N BY HOT MARK
 6. APPLICABLE PRODUCT SPEC NO.: 108-5280, 108-5342

△ [X] 面から2mmの範囲で測定
 2. 嵌合相手ハウジング型: 178747, 917850
 3. 推奨取付ねじ: JIS B1115, B1122 タッピングねじ, なべ2種
 呼び径3, 長さ6mm以下 (締付けトルク; 0.4N-m (4kg-cm) 以下)
 △ 回路番号: 下図参照のこと
 パワー回路 (23) ~ (26)
 シグナル回路 (1) ~ (22)
 △ 適用製品型番のアプリフィックス及びIDマークを
 カワーホットマークにて表示
 6. 適用製品規格番号: 108-5280, 108-5342

A-A dimensions: 8, 4, 6.4, 4.5, 4.5, 6.4, 4.5, 6.4.

B-B dimensions: 7.1, 4, 6.4, 4.5, 6.4, 4.5, 6.4.

Pin layout: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 23, 24, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 25, 26.

52	PRE-TIN x 21 SELECTIVE-TIN [MATTE] SELECTIVE GOLD x 5	---	(18) (19) (20) (21) (22)	BLACK 黒色	2-5178209-2
52	PRE-TIN x 21 SELECTIVE-TIN [MATTE] SELECTIVE GOLD x 5	---	(18) (19) (20) (21) (22)	LIGHT GRAY 銀色	2-5178209-9
2	PRE-TIN x 21 TIN-LEAD SELECTIVE GOLD x 5	---	(18) (19) (20) (21) (22)	BLACK 黒色	2-178209-2
0	PRE-TIN x 26	---	---	LIGHT GRAY 銀色	178209-9
0	PRE-TIN x 26	---	---	ORANGE 橙色	178209-8
MARKING マーキング	SOLDERING SIDE 半田付け部	CONTACT SIDE 接触部側	POWER CIRCUIT NO. パワー回路	SIGNAL CIRCUIT NO. シグナル回路	HOUSING COLOR ハウジング色
	CONTACT FINISH コンタクト仕上げ		CIRCUIT NO. OF GOLD 全メッキ端子使用回路番号		P/N

TOLERANCES UNLESS OTHERWISE SPECIFIED.
 一般公差

10±	±0.2
30±	±0.25
100±	±0.3
> 30	±0.3
ANGLE	±0.3°

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: 単位: 純 mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 一般公差	DWN T.SHINOHARA 02JUN11
		CHK K.BETSUI 02JUN11
		APVD K.BETSUI 02JUN11
		PRODUCT SPEC 製品規格
		APPLICATION SPEC 取付適用規格
MATERIAL 材料	FINISH 仕上	WEIGHT 12.8 g
HOUSING: PBT	SEE TABLE 表参照	CUSTOMER DRAWING
CONTACT: BRASS		

TE Connectivity

26POSITION CAP HOUSING ASSEMBLY
 040/070 SERIES HYBRID I/O CONNECTOR
 LOWPRO FILE

SIZE	CAGE CODE	DRAWING NO. 番号	RESTRICTED TO
A2	00779	C=178209	-
SCALE 尺度	SHEET	REV	
2:1	1 of 1	D4	

1471-9 (1/15)

178209

A