


Part Number: 1617AP

CATV Video, RG11, 14 AWG BCCS, Quad Shield, CMP



Product Description

Series 11, 14 AWG solid .064" bare copper-covered steel conductor, foam FEP insulation, Duobond® IV, aluminum braid shield (Foil + 60% Braid + Foil + 40% Braid), Solef PVDF fluorocopolymer jacket.

Technical Specifications

Product Overview

Environmental Space:	Indoor - Plenum
Suitable Applications:	Direct Broadcast Satellite, DBS, TV, CATV, Off-Air Television, TV Antenna

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
14	Solid	BCCS - Bare Copper Covered Steel	0.064 in	1

Conductor Count:	1
Conductor Size:	14 AWG

Insulation

Material	Nominal Diameter
FFEP - Foam Fluorinated Ethylene Propylene	0.274 in

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Aluminum/Polyester/Aluminum	Bonded Duofoil®	100 %
Braid	2	AL - Aluminum		60 %
Tape	3	Aluminum/Polyester/Aluminum	Duofoil®	100 %
Braid	4	AL - Aluminum		40 %

Outer Jacket Material

Material	Nominal Diameter
PVDF - Fluorocopolymer	0.372 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
11 Ohm/1000ft	3 Ohm/1000ft	3 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Shield
16.3 pF/ft

Shielding:	Multiple or Specialty
------------	-----------------------

Inductance

Nominal Inductance
0.106 µH/ft

Impedance

Nominal Characteristic Impedance
75 Ohm

Return Loss (RL)

Frequency [MHz]	Min. Structural Return Loss (SRL)
5 - 1000 MHz	20 dB
1000 - 2250 MHz	15 dB

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.2 dB/100ft
10 MHz	0.5 dB/100ft
50 MHz	0.9 dB/100ft
100 MHz	1.3 dB/100ft
200 MHz	1.9 dB/100ft
400 MHz	2.8 dB/100ft
700 MHz	3.9 dB/100ft
900 MHz	4.7 dB/100ft
1000 MHz	5 dB/100ft
1450 MHz	6.7 dB/100ft
1800 MHz	7.7 dB/100ft
2250 MHz	8.5 dB/100ft

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.21 ns/ft	83 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)
5 MHz	0.38 dB/100ft
55 MHz	1.12 dB/100ft
211 MHz	2.24 dB/100ft
270 MHz	2.59 dB/100ft
300 MHz	2.75 dB/100ft
350 MHz	3.08 dB/100ft
400 MHz	3.34 dB/100ft
450 MHz	3.64 dB/100ft
550 MHz	4.19 dB/100ft
700 MHz	5.03 dB/100ft
800 MHz	5.51 dB/100ft
870 MHz	5.86 dB/100ft
1000 MHz	6.53 dB/100ft
1450 MHz	8.50 dB/100ft
1800 MHz	10.0 dB/100ft
2250 MHz	11.8 dB/100ft

Voltage

Non-UL Voltage Rating	UL Voltage Rating
300 V RMS	300 V RMS

Temperature Range

Non-UL Temp Rating:	150°C
Operating Temp Range:	-20°C To +150°C

Mechanical Characteristics

Bulk Cable Weight:	62 lbs/1000ft
Max Recommended Pulling Tension:	260 lbs
Min Bend Radius/Minor Axis:	3.75 in

Standards

NEC/(UL) Specification:	CATVP, CMP
CEC/C(UL) Specification:	CMP

RG Type:	11/U Type
Series Type:	Series 11
RG / Series Type:	Series 11

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-07-16
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Flammability, LSOH, Toxicity Testing

UL Flammability:	NFPA 262
CSA Flammability:	FT6
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

Part Number

Non-Plenum Number:	7999A
--------------------	-------

Variants

Item #	Color
1617AP 0101000	
1617AP 0101000	Black

© 2018 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.