

Shrink sleeve - WMS 3,2 (EX5)R YE - 0800301

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Shrink sleeve, Roll, yellow, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK W: without print, unperforated, mounting type: slide on, cable diameter range: 1 - 3.2 mm, lettering field size: 5 x 30000 mm

Why buy this product

- Available in the form of continuous rolls and can be printed on both sides using the THERMOMARK W2 printer
- The shrink sleeves are automatically perforated or cut to the required length during the printing process
- UL 224 (125°C, 600 V, all tubing)
- MIL-STD-202G, SAE AMS-DTL-23053, SAE AS-81531
- CSA.C22.2 No. 198.1 (125°C, 600 V, all tubing)
- Individual markers can be cut to any length up to 1 m

Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 STK |
| GTIN |  4 046356 625982 |
| GTIN | 4046356625982 |

Technical data

Dimensions

| | |
|----------------|-----------------|
| Length (b) | 30 m |
| Width (a) | 5 mm |
| Cable diameter | 1 mm ... 3.2 mm |

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -55 °C ... 135 °C |
|---------------------------------|-------------------|

General

| | |
|-----------------------|---------------|
| Color | yellow |
| Base element material | polyolefine |
| Type | Shrink sleeve |
| Components | halogen-free |

Shrink sleeve - WMS 3,2 (EX5)R YE - 0800301

Technical data

General

| | |
|-------------------------------------|-----------------------------|
| Material | Polyolefine |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Printing | without print |
| Number of individual labels | 1000 |
| Number of individual labels per row | 1 |
| Marking mounting type | slide on |

Standards and Regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |
|------------|---|

Approvals

Approvals

Approvals

CSA / UL Recognized

Ex Approvals

Approval details

| | | | |
|-----|--|---|--------|
| CSA | | http://www.csagroup.org/services-industries/product-listing/ | 252259 |
|-----|--|---|--------|

| | | | |
|---------------|--|---|---------------|
| UL Recognized | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 310982 |
|---------------|--|---|---------------|

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>