т <u></u> П	m	D	0	D	A	
	S			XAMPLE		4
	nown as example					
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal					
-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	A 38.1±0.3 B 23.82+0.1/-0.15 R 32.5Max S 34.9±0.4 W 2.2+0.9/-0.1 VV THREAD M18x1-6g		SOURIAU shall not be liable for any due to a use of the Products wh the Specifications issued by either of (professional recommendat	hich does not comply with f the Parties or by a third party		
-Seals & Grommet : Silicon Elastomer Contact Plating : Gold over copper Alloy 0.8µm minimum			Countr	y Jurisdiction & Control List Not Listed		2
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D713V	V08PC		
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 29-09-2016	First Release			
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAV	MOD N°	<u> </u>
		TITLE	Aluminium	n Receptacle 8D series		
BASIC SERIES: 8D 7 - 13 W 08 P	c	SCALE -	General linear Tolerances:	NPRDS / PROJE	СТ	
SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact	ORIENTATION : C	SOURIAU	WWW.SOURIAU.C	This document is SOUF	RIAU	1
SHELL SIZE : 13			communicated wi	thout permission		
PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 13-08	format A3	SOURIAU 8D713W		SHEET 1/2	
H G F	E	D	C	B	A	

Г	т	G	П	ш	D	0	Φ	A		,
		Contact Layout				Panel cutout				
4	•	$ \begin{array}{c} & & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & $					∧			4
		(Insert arrangement 13-8) Contact location X-axis Y-axis (mm) (mm) A +.065 (1.65) +.157 (3.99) 3 +.170 (4.32) +.000 (0.00) C +.120 (3.05) 120 (3.05) 0 .000 (0.00) 170 (4.32) 5 120 (3.05) 120 (3.05) 5 005 (1.65) +.157 (3.99) 4 +.000 (0.00) +.044 (1.12)				Ø	γ		-	
ω		mber of Size Service Contact Supersede intacts contacts rating location 8 8 20 I All MS20051-				Dim Nominal B 24.26+0/-0. ØC 25.65+0.25,	25			3
	_					SOURIAU shall not be liab due to a use of the Pro	le for any non-conformit ducts which does not cor			
N						the Specifications issued by (professional recor	nmendation, technical no			2
					A 29-09-201	PN: 8D	713W08PC			
					ISS DATE Designed By:	Latest modification - by Date:		CUSTOMER DRAWING	MOD N°	
					TITLE		ninium Receptacl			
_					SCALE NA	Genera Tolera ±		NPRDS / PROJECT 859	hu of	1
					SOURIAU			This document is the proper SOURIAU it must not be reproduced communicated without perm	or	
					FORMAT A3		RIAU DRG N° 13W08PC-C		SHEET 2/2	
L	Н	G	F	E	D	C	<u>B</u>	A		