



UNIT:mm




CABLE BLACK PRINT
 USB CABLE E189529 **RU** AWM 2725 28AWG/1PR AND
 24AWG/2C 80°C 30V VW-1

PIN ASSIGNMENT:



Electrical test:
 1. 100% short, open, miswire test
 2. Conduct resistance: 5 Ohm(max)
 3. Insulation resistance: 5Mohm(min)
 4. dielectric test: DC 300V



1PCS/PE BAG

⑧	PE BAG	1/5	CLEAR SIZE: 330*380*40.05mm PRINT BLACK "MADE IN CHINA" + "5PCS"
⑦	PE BAG	1	CLEAR SIZE: 210*250*40.05mm PRINT BLACK "MADE IN CHINA" + "1PC"
⑥	TIE	1	WHITE L=150mm
⑤	OUT JACKET	6g	BEIGE (1V-29#) PVC-40P (MOULD NO: NM-65)
④	OUT JACKET	6g	BEIGE (1V-29#) PVC-40P (MOULD NO: NM-40)
③	CABLE	1	BEIGE (1V-29#) USB1. 1 UL2725 28#/1P+26#/2C+AEB OD: 4.7mm L=5000±20mm
②	CONN	1set	USB B MALE SHELL: NICKEL PIN G/F 3PCS TYPE INSULATOR COLOR: WHITE
①	CONN	1set	USB A MALE SHELL: NICKEL PIN G/F 4PCS TYPE INSULATOR COLOR: WHITE
NO.	NAME	QTY	SPECIFICATION

CNC Tech, LLC			
Industrial Cable and Connector Technology			
DRAWN	ZHONGHS	DRAWING NO	
CHECKED		CUSTOMER	
APPROVAL		ITEM NO.	101-1030-BE-00500
DECIDED		DATE	2012-02-15
VERSIONS/EDITEDN	A/0	PROJECTION	