



#### General ordering data

Order No.	1680411044
Part designation	TM-I 20 BLANK RT
Version	Conductor markers, L x W: 20 x 4 mm, Polyamide 66, white
EAN	4008190914769
Qty.	400 pc(s).

#### Markings

Cadmium	no
Can be labelled with thermal transfer printers	No
Can be printed with plotter	Yes
Can be written with dot-matrix printer	No
Can be written with laser printer	No
Conductor O.D., max.	40 mm
Conductor O.D., min.	1 mm
Conductor cross-section, max.	500 mm <sup>2</sup>
Conductor cross-section, min.	0.22 mm <sup>2</sup>
Function	Conductor and cable markers
Halogen	no
Height	2 mm
Insulation cross-section, max.	40 mm
Length	20 mm
Material	Polyamide 66
Material colour	white
Material colour according to resistance code	9
Max. temperature, continuous	100 °C
Min. temperature, continuous	-40 °C
Pin can be written (STI)	Yes
PrintJet	Yes
Printed characters	without
Silicone	no
Speed marking laser	Yes
Type of printing	Neutral
UL 94 flammability class	V2

#### Markings

Width 4 mm

#### Approvals

Approvals institutes n.a.

#### Classifications

eClass 4.1	24-19-02-19
eClass 5.0	27-14-91-03
eClass 5.1	27-14-91-03

#### Similar products

Order No.	Part designation	Version
1680411693	TM-I 20 NEUTRAL	Conductor markers, L x W: 20 x 4 mm, Polyamide 66, Blue
1680411687	TM-I 20 BLANK BL	Conductor markers, L x W: 20 x 4 mm, Polyamide 66, yellow
1680411688	TM-I 20 BLANK GE	Conductor markers, L x W: 20 x 4 mm, Polyamide 66, green
1680411686	TM-I 20 BLANK GN	Conductor markers, L x W: 20 x 4 mm, Polyamide 66, red