

## Panel feed-through terminal block - RWV 8 - 3073762

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Panel feed-through terminal block, Connection method: Bolt connection, Load current : 125 A, Cross section: 2.5 mm<sup>2</sup> - 35 mm<sup>2</sup>, AWG 14 - 2, Connection direction of the conductor to plug-in direction: 90 °, Width: 20.3 mm, Color: gray

### Product Features

- ✓ Easy grouping with engagement pin versions
- ✓ Quick and easy conductor connection thanks to hinged cover flaps with captive clamping nut
- ✓ Both terminal halves can be easily assembled by simply snapping them together
- ✓ Spring-loaded spacers protect the bolt connection against loosening
- ✓ Molded versions ensure maximum tightness of seal
- ✓ Touch-proof insulating housing in a new design
- ✓ Automatic compensation of the panel thickness via the snap principle integrated in the insulation housing



### Key commercial data

|                                      |           |
|--------------------------------------|-----------|
| Packing unit                         | 1 1       |
| Minimum order quantity               | 10 1      |
| Weight per Piece (excluding packing) | 100.0 GRM |
| Custom tariff number                 | 85369010  |
| Country of origin                    | China     |

### Technical data

#### General

|   |       |
|---|-------|
| Number of levels                        | 1     |
| Number of connections                   | 2     |
| Color                                   | gray  |
| Insulating material                     | PA    |
| Inflammability class according to UL 94 | V0    |
| Maximum load current                    | 125 A |
| Rated surge voltage                     | 6 kV  |

## Panel feed-through terminal block - RWV 8 - 3073762

### Technical data

#### General

|                                  |               |
|----------------------------------|---------------|
| Pollution degree                 | 3             |
| Surge voltage category           | III           |
| Insulating material group        | I             |
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal current $I_N$            | 125 A         |
| Nominal voltage $U_N$            | 1000 V        |
| Open side panel                  | nein          |
| Number of positions              | 1             |

#### Dimensions

|       |         |
|-------|---------|
| Width | 20.3 mm |
|-------|---------|

#### Connection data

|  |                         |
|--|-------------------------|
| Note                                   | Connection bolts        |
| Connection side                        | Level 1 above 1 below 1 |
| Connection method                      | Bolt connection         |
| Conductor cross section solid min.     | 2.5 mm <sup>2</sup>     |
| Conductor cross section solid max.     | 35 mm <sup>2</sup>      |
| Conductor cross section stranded min.  | 2.5 mm <sup>2</sup>     |
| Conductor cross section stranded max.  | 35 mm <sup>2</sup>      |
| Conductor cross section AWG/kcmil min. | 14                      |
| Conductor cross section AWG/kcmil max  | 2                       |
| Screw thread                           | M8                      |
| Tightening torque, min                 | 4.5 Nm                  |
| Tightening torque max                  | 5 Nm                    |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141131 |
| eCl@ss 4.1 | 27141131 |
| eCl@ss 5.0 | 27141134 |
| eCl@ss 5.1 | 27141134 |
| eCl@ss 6.0 | 27141134 |
| eCl@ss 7.0 | 27141134 |
| eCl@ss 8.0 | 27141134 |

# Panel feed-through terminal block - RWV 8 - 3073762

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC001283 |
| ETIM 3.0 | EC001283 |
| ETIM 4.0 | EC001283 |
| ETIM 5.0 | EC001283 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

## Approvals

### Approvals

---

#### Approvals

UL Recognized / GOST / GOST

---

#### Ex Approvals

---

#### Approvals submitted

---

## Approval details

|                                |       |       |
|--------------------------------|-------|-------|
| UL Recognized                  |       |       |
|                                | B     | C     |
| Nominal current I <sub>N</sub> | 115 A | 115 A |
| Nominal voltage U <sub>N</sub> | 600 V | 600 V |

|      |  |  |
|------|--|--|
| GOST |  |  |
|------|--|--|

## Panel feed-through terminal block - RWV 8 - 3073762

### Approvals



### Accessories

#### Accessories

#### Flange

Flange cover - RWV 8-F - 3075333



Flange cover, Color: gray

#### Screwdriver tools

Screwdriver - SZS 1,0X6,5 VDE - 1205079



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 6.5 x 150 mm, 2-component grip, with non-slip grip

#### Terminal marking

Marker for terminal blocks - TMT (EX9,5)R - 0828295



Marker for terminal blocks, Roll, white, Unlabeled, Can be labeled with: THERMOMARK ROLL, THERMOMARK X, THERMOMARK S1.1, Mounting type: Snap into universal marker groove, Snap into flat marker groove, Lettering field: 9.5 x 50000 mm

Zack marker strip - ZB 20,3:UNPRINTED - 0820248



Zack marker strip, Strip, white, Unlabeled, Can be labeled with: Plotter, Mounting type: Snap into tall marker groove, For terminal block width: 20.3 mm, Lettering field: 10.5 x 20.25 mm

# Panel feed-through terminal block - RWV 8 - 3073762

## Accessories

Zack marker strip - ZB 16,3:UNPRINTED - 0820222



Zack marker strip, Strip, white, Unlabeled, Can be labeled with: Plotter, Mounting type: Snap into tall marker groove, For terminal block width: 16.3 mm, Lettering field: 10.5 x 16.25 mm

## Drawings

