


Specification Sheet

Part Number: MB3A0A2H4



Adhesive Base, .75" x .75", .14" Max Tie Width, .12" Hole Dia, PA66/Acrylate, Black, 500/pkg

Article Number

151-28709

Type

MB3A

Color

Black (BK)

Features & Benefits

- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
- Secures with acrylic based adhesive backing for heavy bonding applications
- Can also be secured using two or four screws; providing multiple options.
- 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

Quantity Per

bag

Product Description

HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

Short Description	Adhesive Base, .75" x .75", .14" Max Tie Width, .12" Hole Dia, PA66/Acrylate, Black, 500/pkg
Global Part Name	MB3A-PA66-BK
Length L (Imperial)	0.75
Length L (Metric)	19.0
Fixation Method	Screw Mounting and Adhesive
Width W (Imperial)	0.75
Width W (Metric)	19.0
Cable Ties	T18 - T30
Height H (Imperial)	.19
Height H (Metric)	4.80
Cable Tie Width Max (Imperial)	0.14
Cable Tie Width Max (Metric)	3.6
Mounting Hole Diameter D (Imperial)	0.12
Mounting Hole Diameter D (Metric)	3.0 mm
Mounting Hole Diameter D Max (Metric)	3.0
Mounting Hole Centers (Imperial)	0.52

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Adhesive	Acrylate with base of acrylic foam
Flammability	UL 94 V2 (excluding adhesive)
Adhesive Operating Temperature	to +194°F (+90°C)
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
ROHS Complaint	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909987