

#### General ordering data

Order No.	1775560000
Part designation	ZPE 1.5/3AN
Version	Earth terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, green/yellow, TS 35
EAN	4032248181223
Qty.	100 pc(s).

#### Product notes

Product description	Z-series standard ranges provide solutions for conductor cross-sections from 0.05 to 35 mm <sup>2</sup> .
---------------------	---

#### PT OKIECEEx/ATEX rating data

EU-type examination certificate	KEMA01ATEX2106U
Download, German	KEMA01ATEX2106U_d.pdf
Download English	KEMA01ATEX2106U_e.pdf
IECEX Certificate of Conformity	IECEXULD05.0009U
Download	IECEXULD05.0009U_e.pdf
ATEX conductor cross-section	1.5 mm <sup>2</sup>
IECEX conductor cross-section	1.5 mm <sup>2</sup>
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	Einsatztemperaturbereich siehe EG-Baumusterprüfbescheinigung/IECEX-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

#### Additional technical data

Colour of insulating material	green/yellow
Connection direction	top
End plate required	Yes
Explosion-tested version "Ex e"	Yes
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No

**Additional technical data**

No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	3
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Clamped
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	PE terminal

**CSA rating data**

Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 14

**Conductors for clamping (additional connection)**

Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	1.5 mm <sup>2</sup>

**Conductors for clamping (rated connection)**

Clamping range, min.	0.05 mm <sup>2</sup>
Clamping range, max.	1.5 mm <sup>2</sup>
Type of connection	Tension clamp connection
2nd type of connection	clamped
Connection direction	top
No. of connections	3
Stripping length	10 mm
Blade size	0.4 x 2.0 mm
Gauge to IEC 60947-1	B1
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	1.5 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	1.5 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	1.5 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	1.5 mm <sup>2</sup>
Twin wire-end ferrule, min.	0.5 mm <sup>2</sup>
Twin wire end ferrule, max.	0.75 mm <sup>2</sup>
AWG conductor size, min.	AWG 28
AWG conductor size, max.	AWG 16
AWG conductor size, min.	0.08 mm <sup>2</sup>
AWG conductor size, max.	1.31 mm <sup>2</sup>

**Dimensions**

Width	3.5 mm
Height of lowest version	37 mm
Length	63 mm

#### Dimensions

TS 35 offset 30 mm

#### PE rating data


PEN function No  
 Pollution severity 3  
 Rated cross-section 1.5 mm<sup>2</sup>  
 Rated impulse withstand voltage to adjacent terminal 6 kV  
 Rated short-time current 180 A (1,5 mm<sup>2</sup>)  
 Rated voltage for adjacent terminal 500 V  
 Standards IEC 60947-7-2

#### UL rating data

Min. cross-section (UL) AWG 30  
 Max. cross-section (UL) AWG 14

#### Approvals

Approvals institutes



#### Downloads

STEP 1775560000\_31266\_ZPE\_1.5-3AN\_STP.stp

#### Classifications

eClass 4.1 27-14-03-05  
 eClass 5.0 27-14-03-05  
 eClass 5.1 27-14-03-05

#### Similar products

Order No.	Part designation	Version
1791150000	ZDK 1.5PE	Earth terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, green/yellow, TS 35
1775510000	ZPE 1.5	Earth terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, green, TS 35
1775620000	ZPE 1.5/4AN	Earth terminal, 1.5 mm <sup>2</sup> , Tension clamp connection, Wemid, green/yellow, TS 35