



**SULLINS ELECTRONICS  
CORP**

SAN MARCOS, CA 760-744-0125 FAX  
760-744-6081



C = 4.890+-0.015 [124.21+-0.38]  
F = 2.140+-0.005 [54.36+-0.13]  
G = 2.490+-0.005 [63.25+-0.13]

>



Guide Posts after Positions 42 and 91  
Card Slot Barrier after Position 42

.012x.018 [.30x.46] Staggered Hairpin Bellows Contacts Not Shown



- 1.0 SPECIFICATIONS FOR A DUAL 91/182 POSITION EDGE CARD CONNECTOR
- 2.0 INSULATION MATERIAL: RYTON
- 3.0 CONTACT MATERIAL: CA510 PHOSPHOR BRONZE GRADE C
- 4.0 TEMPERATURE: TO 125 DEGREES C CONTINUOUS
- 5.0 PLATING: .000010" GOLD ON HEADS, .000100" TIN ON TAILS, .000050" NICKEL UNDERPLATE
- 6.0 UL FLAMMABILITY RATING: 94V-0
- 7.0 VOLTAGE RATING: 125 VDC MINIMUM AT SEA LEVEL
- 8.0 CURRENT RATING: 1 AMPERE
- 9.0 INSULATION RESISTANCE: 1,000 MEGA OHMS
- 10.0 BOARD THICKNESS ACCOMMODATED: .054 INCH TO .074 INCH
- 11.0 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
- 12.0 NOT DRAWN TO SCALE

**PART NUMBER: RZB91DCHN-S578**

**DATE: 3-9-04**

[Print PDF](#)