



| PANEL THICKNESS | X |
|-----------------|--------------------------|
| 0.75-1.25 | [0.30-.049] 19.2 [0.756] |
| 1.25-2.0 | [0.49-.079] 19.4 [0.764] |
| 2.0-3.0 | [0.79-.118] 19.8 [0.780] |



| SWITCH FUNCTION | POS. 1 | POS. 2 |
|-----------------|--------|--------|
| <DN> | DNF | |
| 1-1a | OPEN | |



CIRCUIT: SPST

< > = MOMENTARY

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. RATING: 15A @ 125VAC OR
6A @ 250VAC
5. MATERIALS: TERMINALS: Silver Plated Copper Alloy
CONTACTS: Coin Silver, Silver Plated
6. ELECTRIC LIFE: 10,000 cycles
7. CONTACT RESISTANCE: <20 Mega Ω
8. INSULATION RESISTANCE: >1000 Mega Ω
9. DIELECTRIC STRENGTH: >1500 V 1 minute
>3000 V between poles

E-SWITCH®

| | | | | |
|------|---------|-------------------|---------|------|
| B | 11673 | REVISED & REDRAWN | 9/26/01 | CJB |
| REV. | ECN No. | DESCRIPTION | DATE | CHKD |

| | | | | | |
|--------------------|-------|---------|----|---------|-----|
| TITLE | SCALE | DATE | DR | DWG | REV |
| R1966F BLK BLK F S | 1.5:1 | 9/26/01 | CB | M304204 | B |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED