

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION

COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
DF	XO	O	RELEASED	10-02	CT RG

COMPONENT	MATERIAL	FINISH
HOUSING	STAINLESS STEEL PER ASTM-A-484 OR ASTM-A-582 TYPE 303	GOLD PLATED PER ASTM-B-488 OVER NICKEL PER QQ-N-290
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	-
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 ALLOY C17300, CONDITION H	GOLD PLATED PER ASTM-B-488 OVER COPPER PER MIL-C-14550
CONTACT SLEEVE	BERYLLIUM COPPER PER ASTM-B-196 ALLOY C17300, CONDITION H	GOLD PLATED PER ASTM-B-488 OVER NICKEL PER QQ-N-290
CONTACT RING	BERYLLIUM COPPER PER ASTM-B-194 ALLOY C17200, CONDITION H	GOLD PLATED PER ASTM-B-488 OVER COPPER PER MIL-C-14550

ENVIRONMENTAL

TEMPERATURE RATING: -65°C TO +125°C

VIBRATION: MIL-STD-202, METHOD 204, CONDITION D

SHOCK: MIL-STD-202, METHOD 213, CONDITION 1

MOISTURE RESISTANCE: MIL-STD-202, METHOD 106

CORROSION: MIL-STD-202, METHOD 101, CONDITION B.

THERMAL SHOCK: MIL-STD-202, METHOD 107, CONDITION B

MECHANICAL

INTERFACE DIMENSIONS: MIL-C-39012

RECOMMENDED MATING TORQUE: N/A

FORCE TO ENGAGE & DISENGAGE (IN-LBS MAX): 1.5

WEIGHT (GRAMS): TBD

MATING CHARACTERISTICS: INSERTION (MAX LBS): 3.0
WITHDRAWAL (MIN OZ): 1.0

CABLE RETENTION: AXIAL FORCE (LBS): N/A
TORQUE (IN-OZ): N/A

CENTER CONTACT CAPTIVATION: AXIAL (LBS): 6.0
RADIAL (IN-OZ): N/A

ELECTRICAL

NORMAL IMPEDANCE (OHMS): 50

FREQUENCY RANGE (GHz): DC TO 18

VOLT RATING @ SEA LEVEL (VRMS MAX): 335

VSWR: N/A

INSERTION LOSS: (dB MAX): N/A

RF LEAKAGE (dB MIN): N/A

CORONA 70,000 FT (VRMS MIN): 250

DIELECTRIC WITHSTANDING VOLTAGE (VRMS MIN) AT SEA LEVEL: 1,000

I.R. (MEGOHMS MIN): 5,000

RF HIGH POTENTIAL AT SEA LEVEL (VRMS MIN @ 5 MHz): 670

CONTACT RESISTANCE (MILLIOHMS MAX): CENTER CONTACT: 2.0
OUTER CONTACT: 2.0
CABLE TO HOUSING: N/A

Dimensions: .570 [14.48], .375 [9.53], .195 [4.95] REF, .065 [1.65], .197 [5.00] REF, .050 [1.27]

Labels: MOUNTING SURFACE, REF PLANE

Dimensions: .200 [5.08] TYP, .100 [2.54] TYP, .030 [0.76] SQUARE 4 PLC

Label: $\phi .375$ [9.52]

Dimensions: $\phi .067^{+.003}_{-.000}$ [1.70 +0.08 / -0.00] 5 PLC, .200 [5.08] TYP

RECOMMENDED MOUNTING PATTERN

1663069-1
PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C.C.THOMAS 10-3-02	Tyco Electronics Corporation Harrisburg, PA 17105																		
DIMENSIONS: INCHES		CHK R.GROSS 10-3-02																			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD R.GROSS 10-3-02	NAME OSP PWB STRAIGHT PCB JACK STRAIGHT TERMINAL,RF																		
<table border="1"> <tr><td>0 PLC</td><td>±</td><td>-</td></tr> <tr><td>1 PLC</td><td>±</td><td>-</td></tr> <tr><td>2 PLC</td><td>±</td><td>-</td></tr> <tr><td>3 PLC</td><td>±</td><td>.005 [0.13]</td></tr> <tr><td>4 PLC</td><td>±</td><td>-</td></tr> <tr><td>ANGLES</td><td>±</td><td>-</td></tr> </table>		0 PLC	±	-	1 PLC	±	-	2 PLC	±	-	3 PLC	±	.005 [0.13]	4 PLC	±	-	ANGLES	±	-	PRODUCT SPEC APPLICATION SPEC	SIZE A2
0 PLC	±	-																			
1 PLC	±	-																			
2 PLC	±	-																			
3 PLC	±	.005 [0.13]																			
4 PLC	±	-																			
ANGLES	±	-																			
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT -	CAGE CODE 00779																		
CUSTOMER DRAWING		DRAWING NO. 1663069	RESTRICTED TO -																		
		SCALE 10:1	SHEET 1 OF 1																		
		REV 0																			

AMP 1471-9 REV 31MAR2000

H:\docmod\

1663069