





Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriete de c FCI. Droits de reproduction FCI.



All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.



**PERFORMANCE CHARACTERISTICS**

CURRENT RATING 1.5A AT 20°C (FULLY LOADED)  
 1 A AT 70°C (FULLY LOADED)  
 RATED VOLTAGE : 500 V AC (CONT /CONT)  
 OPERATING TEMPERATURE : -55°C TO 125°C  
 CONTACT RESISTANCE 20 mΩ MAX INSULATION RESISTANCE : 10<sup>4</sup> MΩ MIN  
 INSERTION FORCE : 0.75N MAX/CONT EXTRACTION FORCE : 0.15N MIN/CONT

**NOTES**

1.HM2S30PE5100  
 LEAD FREE INDICATOR : LF=LEAD FREE(DIGIT 15&16)  
 PLATING CODE(DIGIT 13&14)

Plating code	Plating	Performance Level
AA	0.75µm Au	IEC performance level 2(250mating cycles)orTELCORDIA CO)
AB	1.25µm Au	TELCORDIA UE

- THIS PRODUCT IS CSA APPROVED. THIS PRODUCT IS UL RECOGNIZED.
- FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS.A.201572.001
- THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

rev	ecn no	dr	date
A	DG09-0243	NZ	Jul-20-2009
B	DG10-0093	NZ	Mar-08-2010
C	DG10-0110	NZ	Jun-08-2010
-	-	-	-
-	-	-	-
-	-	-	-

Material		Spec ref			
Mat code		<input checked="" type="checkbox"/> tolerance IDECC±0.2 IDECC 2DECC±0.1 2DECC ANGLESEIT* HOEKEN	projection 	MM	
Heatreat					
Plating/Finish					
Dr	Nickor Zuo	Jul-20-09	size	A4	
Eng	Nickor Zuo	Jul-20-09	Product family	MILLIPACS	
Chr	PeiMing Zheng	Jul-20-09	Model Name	ECN	
Appr	Joseph Hsia	Jul-20-09	Model Revision	REL Level	
		title MILLIPACS 2/TYPE C(W/O LOC.PEG) / NO SHIELDING		dwg no BSC201418017	Rev. C
Pro/E file	catalog no	HM2S30PE5100----	CUMSTOMER DRAWING	sheet 1 of 1	