

# 150mw Audio Miniature Epoxy Potted *107 Series*

PC Board Mount

## Features



- Perfect for audio input, line matching, isolation or output transformer applications.
- 150 milliwatt (+/- 1.5 db, 300 Hz. - 50 KHz.)
- Epoxy potted in an attractive black molded case, Pin type P.C. board mount (min. 0.187" length).
- In some models where no center tap is required (on secondary), pin No. 5 is omitted.
- Power level ratings are maximum at lowest frequency rating (see charts & PDF spec. sheets below)
- Power can be increased slightly at higher frequencies (except 107X). See individual PDF specs. for specifics.
- Will withstand soldering for 10 sec. @ 260 degrees C, ambient temp. 85 degrees C max.

Part No.	Nominal Impedance (Ohms)		D.C. Resistance (Ohms) +/- 20%		Max. D.C. Unbalance (ma.)
	Primary (Pins 1-3)	Secondary (Pins 4-6)	Primary (Pins 1-3)	Secondary (Pins 4-6)	
<b>107B</b>	150 ct	12	20	2	12
<b>107D</b>	150 ct	150 ct	20	25	12
<b>107E</b>	600 ct	3.2	59	0.6	6
<b>107G</b>	600 ct	250 ct	59	10	6
<b>107H</b>	600 ct	600 ct	59	75	6
<b>107J</b>	1K ct	600 ct	92	71	4.5
<b>107L</b>	10K ct	3.2	780	0.65	1.5
<b>107N</b>	10K ct	600 ct	680	70	1.5
<b>107P</b>	10K ct	1.5K ct	680	150	1.5
<b>107R</b>	10K ct	4K ct	680	390	1.5
<b>107T</b>	10K ct	10K ct	680	700	1.5
<b>107V</b>	25K ct	600 ct	1300	70	1
<b>107X</b>	100K ct	1K ct	3700	80	0

*Data subject to change without notice*