

Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case that the application demands a high level of reliability, such as automotive, please contact a company representative for further information.

△	△	△	△	△	△	△	△	△	△
COUNT	REVISIONS	BY	CHKD	DATE	COUNT	REVISIONS	BY	CHKD	DATE
△					△				
△					△				

APPLICABLE STANDARD			
RATING	VOLTAGE	CONTACT No. — — —	AC — V DC — V
	CURRENT	CONTACT No. — — —	2 A
	POWER		
	SPECIALTY		
APPLICABLE CABLES		AWG #26~#30 (Insulation Dia 1 Max)	
IMPEDANCE FREQUENCY RANGE		— Ω (0 ~ — Hz)	
OPERATING TEMPERATURE RANGE		-15 °C ~ +60 °C	

SPECIFICATIONS

No.	ITEM	CONDITIONS	TEST STANDARD	MIN	MAX	UNITS	QT	AT
1	DESIGN-MATERIAL-FINISH	ADC		—	—	—	○	○
2	MARKING	Applicable Std. and DC 3-21313		—	—	—	○	○
3	INSULATION RESISTANCE	Must be over standard value at DC V.		—	—	MΩ	—	—
4	CONTACT RESISTANCE	The voltage drop must be under the Std. value at DC 1 A.		—	10	mΩ	○	—
	CONTACT	The voltage drop must be under the Std. value at DC A.		—	—	mΩ	—	—
5	DIELECTRIC WITHSTANDING VOLTAGE	Must keep the AC DC V for one minute.		—	—	—	—	—
6	V SWR	Must be under the Std. value at frequency ~ Hz.		—	—	—	—	—
7	INSERTION LOSS	Must be under the Std. value at frequency ~ Hz.		—	—	dB	—	—
8	LOW LEVEL CIRCUIT	The Contact Resistance must be under the Std. value at DC 20mV less and mA.		—	—	mΩ	—	—
9	CONTACT ENGAGEMENT AND SEPARATION FORCES	Must be suitable for the Std. value at applicable gauge. gauge size φ0.53±0.003		15	—	gf	○	—
	MATING AND UNMATING FORCES	Must be suitable for the Std. value.		—	—	kgf	—	—
10	HUMIDITY	Insulation resistance must be over the Std. value at τ ~ % hours.	at high humidity	—	—	MΩ	—	—
			after high humidity	—	—	MΩ	—	—
11	VIBRATION	Must have no damage, crack and looseness of parts at Frequency range ~ Hz. Total amplitude mm, G at hours for directions.		—	—	—	—	—
12	SHOCK	Must have no damage, crack and looseness of parts G at times for directions.		—	—	—	—	—
13	TEMPERATURE CYCLING	Must have no damage, crack and looseness of parts for ~ °C cycles.		—	—	—	—	—
14	DURABILITY	Must be less than the Std. value after 1000 times insertion and extraction at the condition described in above item No.4.	JIS C 5037	—	15	mΩ	○	—
	CONTACT			—	—	mΩ	—	—
15	SALT SPRAY (CORROSION)	Must not have heavy corrosion after 5 x salt water spray for 48 hours.	JIS C 5028	—	—	—	○	—
16	WATER PRESSURE WITHSTANDING	No leakage at depth m kof/cm ² hours.		—	—	—	—	—
17	AIR PRESSURE WITHSTANDING	No leakage at pressure kof/cm ² mmHg		—	—	—	—	—
18	Crimped termination Conductor tensile Strength.	The only Conductor part of suitable cable shall be crimped with the wire, on extraction force is applied which is more than the standard.	AWG #30 (7/0.1)	1	—	kgf	○	—
			AWG #28 (7/0.12)	1.6				
			AWG #26 (7/0.16)	2.4				

REMARKS	APPROVED	<i>M. Yoshida</i>	7.23.91	ISSUED BY HR5 HIROSE ELECTRIC CO., LTD.
	REVIEWED			
	CHECKED	<i>M. Sato</i>	4.23.91	
	DESIGNED	<i>M. Onodera</i>	4.16.91	
	DRAWN	<i>E. Kawamura</i>	4.12.91	
DRAWING No. SLC4-21313 - SPECIFICATION SHEET			PART No. HR12-SC-212	CODE No. CL112-0408-9-