

LD44TT3

Thermal Transfer Label, 4.0" X 4.0", Paper, White, 1500/RL

Article Number: 596-00337

Part Number: LD44TT3

Type: LD44TT3

[→ Find a Distributor](#)[→ Order Samples](#)[→ Get Technical Drawings](#)

- ▶ [Cable Ties](#)
- ▶ [Cable Ties with Fasteners](#)
- ▶ [Cable Tie Tools](#)
- ▶ [Clamps and Clips](#)
- ▶ [Heatshrink Moulded Shapes](#)
- ▶ [Mounts](#)
- ▶ [Heavy Duty Mounts](#)
- ▶ [Wire Connectors](#)
- ▶ [Wiring Duct](#)
- ▶ [Wiring Protection](#)
- ▶ [Labels, Printers and Software](#)
- ▶ [Pre-Terminated Networking](#)
- ▶ [Copper Network Solutions](#)
- ▶ [Fiber Network Solutions](#)
- ▶ [Jacks and Wall Plates](#)
- ▶ [Racks - Cable Management](#)
- ▶ [Surface Raceway Systems](#)

[→ Base Data](#)

Part No.	LD44TT3
Type	LD44TT3
Color	White (WH)
Features	<ul style="list-style-type: none"> HellermannTyton Thermal Transfer Paper labels are ideal for temporary applications due to low cost. The labels come in the most common sizes to fit most packaging applications.
Application Method	Labels are printed using a HellermannTyton thermal transfer printer and then applied by hand.

[→ Product Dimensions](#)

Length (L)	4.0" / 101.6mm
Width (W) (imperial)	4.0"
Width (W)	101.6mm
Height (H)	4.0" / 101.6mm
Height (H2)	4" / 101.6mm
Print Method	Thermal Transfer

[→ Material and Specifications](#)

Material	Paper (PAP)
Operating Temperature	-40 °F to +180 °F (-40 °C to +82 °C)
ROHS Conformity	

[→ Logistic and Packaging](#)

Packaging Type	case
Pkg. Qty.	1 / 1
UPC	089306182177

[Find a Distributor](#)[Get Product Samples](#)[Get Technical Drawings](#)

