



# 775 Combination Carbon Monoxide & Combustion Gas Leak Detector

**New!  
Two Tools  
in One!**

The TPI 775 is a state-of-the-art Carbon Monoxide and Combustible Gas Leak Detector. It is the first of its kind to combine both detection technologies into one easy to use hand-held affordable instrument.



The TPI 775 is a state-of-the-art Carbon Monoxide and Combustible Gas Leak Detector. It is the first of its kind to combine both detection technologies into one easy to use hand-held and affordable instrument.

- Easy to use
- One hand operation
- Auto zero
- Back light
- Visible and audible alarm

Turn over for technical information and accessory part numbers.

**The Value Leader™**

## Sensor Specifications

Type	Resolution	Range	Accuracy
Leak	<50ppm	0-50,000ppm	±10%
CO	1ppm	0-2,000ppm	±5ppm or 5%; whichever is greater



## TECHNICAL SPECIFICATIONS AND ACCESSORIES

- Digital Multimeters
- Clamp Meters
- Hand-held Oscilloscopes
- Refrigerant & Combustible Gas Leak Detectors
- Temperature Testers
- BNC Coax Cable Connectors
- Test Leads
- Accessories

### Test Products

#### International, Inc.

Headquarters:  
9615 SW Allen Blvd.  
Beaverton, OR 97005  
USA  
503-520-9197  
Fax: 503-520-1225  
email:  
info@tpi-thevalueleader.com

### Test Products

#### International, Ltd.

342 Bronte St. South  
Unit 9  
Milton, Ontario L9T  
5B7  
Canada  
905-693-8558  
Fax: 905-693-0888  
email:  
info@tpicanada.com

### Test Products

#### International UK Ltd.

Longley House, East Park  
Crawley, West Sussex  
RH10 6AP England  
Tel: +44 (0)1293 561212  
Fax: +44 (0)1293813465  
contactus@tpieurope.com

## 775 Combustion Carbon Monoxide & Combustion Gas Leak Detector

### SPECIFICATIONS

Alarms	Visual and Audible
Response Time:	
CO	90% in 30 seconds
Leak	Instantaneous
Goose Neck Length	16" (406mm)
Dimensions	9.5" x 2.9" x 2.2" (240mm x 74mm x 55mm)
Power	2 'C' Alkaline Batteries
Power Consumption	About 400mW in typical use
Operating and Storage Temperature	32° to 120°F (0° to 50°C)
Warranty	3 years
Standard Accessories	Soft Carrying Case Manual 2 'C' Alkaline Batteries
Optional Accessories	Earphones

### SENSOR SPECIFICATIONS

Type	Resolution	Range	Accuracy
Leak	<50ppm	0-50,000ppm	±10%
CO	1ppm	0-2,000ppm	±5ppm or 5%; whichever is greater

### Distributed By:



To learn about the entire line of TPI products visit:

[www.tpi-thevalueleader.com](http://www.tpi-thevalueleader.com)

L 775-1104

Copyright © 2004 Test Products International, Inc.