

Specification Sheet

Part Number: T30RA30OHS



Cable Ties for AT2060, 30lb Tensile Strength, PA66HS, Black, 30/bandolier, 600/pkg

Article Number	103-00003
Type	T30RA
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.• Available in reels of 3,000 each or bandoliers of 30 each.
Quantity Per	bag
Product Description	Includes AT2060 tool, power supply, power cord, tool cord, and maintenance and operation manual.
Short Description	Cable Ties for AT2060, 30lb Tensile Strength, PA66HS, Black, 30/bandolier, 600/pkg

Global Part Name

T30RA-PA66HS-BK

Minimum Tensile Strength (Imperial)

30.0

Minimum Tensile Strength (Metric)

133.4

Length L (Imperial)

6.0

Length L (Metric)

152.4

Identification Plate Position

none

Reel Diameter (Imperial)

17.7

Reel Diameter (Metric)

450.0

Reel Width (Imperial)

7.197

Reel Width (Metric)

182.8

Voltage Range

27 Volt

Releasable Closure

No

Width W (Imperial)

0.14

Width W (Metric)

3.6

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.5

Bundle Diameter Max (Imperial)

1.25

Bundle Diameter Max (Metric)	31.75
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.2
Cycle Time	1.2 seconds
Power Supply	Electrical
Tension Force	Adjustable
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +275°F (-40°C to +135°C)
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	600
Package Quantity (Metric)	600
Customs Number	3926909987

Weight (Metric) 1.8

Weight (Imperial) 3.9

Reel Weight (Imperial) 7

Reel Weight (Metric) 3.175