



NOTES:

1. ALL DIMENSION IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. CONTACT RATING SWITCHING: 150mA, 250V AC/DC
350mA, 110V AC/DC
5. OPERATING FORCE: 425±100 CM/STANDARD
6. OPERATING TEMP: -30° to 85°C
7. CIRCUIT SP: 8 POSITIONS, 30° INDEX.
8. DIELECTRIC STRENGTH: 1000V RMS min. @Sea Level
9. TIMING: BBM (Non-Shorting) Break Before Make.
10. HARDWARE SUPPLIED ON SWITCH- SEE BELOW
STOP RING, LOCKWASHER, & HEXNUT
11. ▲ DENOTES CRITICAL PARAMETER.

| | | | | | | | |
|------|---------|-------------|-------------------------|---------|------|----------------|---------|
| A | | 13083 | RELEASED FOR PRODUCTION | 4/24/03 | AR | TITLE | |
| REV. | ECN No. | DESCRIPTION | | DATE | CHKD | KC18A10.001NLS | |
| A | | 13083 | RELEASED FOR PRODUCTION | 4/24/03 | AR | SCALE | 1.5:1 |
| A | | 13083 | RELEASED FOR PRODUCTION | 4/24/03 | AR | DATE | 4/24/03 |
| A | | 13083 | RELEASED FOR PRODUCTION | 4/24/03 | AR | DR | AR |
| A | | 13083 | RELEASED FOR PRODUCTION | 4/24/03 | AR | DWG | G530158 |
| A | | 13083 | RELEASED FOR PRODUCTION | 4/24/03 | AR | REV | A |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED