

## Specification Sheet

Part Number: 151-01632



VHB Adhesive Base, 1.12" x 1.12", .18" Max Tie Width, .18" Hole Dia, PA66HIRHSUV/Acrylic, Black, 500/pkg

**Article Number**

151-01632

**Type**

MB4A

**Color**

Black (BK)

**Features & Benefits**

- For use with 18 through 50 pound HellermannTyton cable ties.
- Extremely durable adhesive achieves high pull-off force and is unaffected by vibration.
- Multiple sizes accommodate a range of cable ties.
- 4-way opening allows cable ties to be installed parallel or perpendicular to wire bundles.
- Predrilled holes extend mounting options and security.
- Mount made of proprietary, impact-modified PA66 material for extraordinary durability, and is heat stabilized and UV resistant for extended life outdoors.
- Peel and stick for quick, convenient use in extreme-duty applications.

**Quantity Per**

bag

**Product Description**

HellermannTyton offers adhesive mounts in a variety of sizes to match your cable tie size and extreme-duty application needs. The mount features 3M™ VHB™ (Very High Bond) adhesive, which actually builds strength over time and holds securely to difficult materials such as aluminum, steel, plastics and painted and powder-coated surfaces.

**Short Description**

VHB Adhesive Base, 1.12" x 1.12", .18" Max Tie Width, .18" Hole Dia, PA66HIRHSUV/Acrylic, Black, 500/pkg

**Global Part Name**

MB4A-PA66HIRHSUV-BK

**Length L (Imperial)**

1.12

**Length L (Metric)**

28.5

**Fixation Method**

Adhesive

**Width W (Imperial)**

1.12

**Width W (Metric)**

28.5

**Cable Ties**

T18 - T50

**Height H (Imperial)**

.22

**Height H (Metric)**

5.60

**Cable Tie Width Max (Imperial)**

0.18

**Cable Tie Width Max (Metric)**

4.6

**Mounting Hole Diameter D (Imperial)**

0.18

**Mounting Hole Diameter D (Metric)**

4.6 mm

|  |      |
|--|------|
| <b>Mounting Hole Diameter D Min (Imperial)</b> | 0.18 |
|--|------|

|  |      |
|--|------|
| <b>Mounting Hole Diameter D Max (Imperial)</b> | 0.18 |
|--|------|

|  |     |
|--|-----|
| <b>Mounting Hole Diameter D Max (Metric)</b> | 4.6 |
|--|-----|

|   |     |
|---|-----|
| <b>Mounting Hole Centers (Imperial)</b> | 0.8 |
|---|-----|

|                 |  |
|-----------------|--|
| <b>Material</b> | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
|-----------------|--|

|                          |             |
|--------------------------|-------------|
| <b>Material Shortcut</b> | PA66HIRHSUV |
|--------------------------|-------------|

|                 |              |
|-----------------|--------------|
| <b>Adhesive</b> | Acrylic foam |
|-----------------|--------------|

|                     |          |
|---------------------|----------|
| <b>Flammability</b> | UL 94 HB |
|---------------------|----------|

|                                       |                                  |
|---------------------------------------|----------------------------------|
| <b>Operating Temperature (Metric)</b> | -40°F to +176°F (-40°C to +80°C) |
|---------------------------------------|----------------------------------|

|                       |     |
|-----------------------|-----|
| <b>ROHS Complaint</b> | Yes |
|-----------------------|-----|

|                                   |     |
|-----------------------------------|-----|
| <b>Package Quantity(Imperial)</b> | 500 |
|-----------------------------------|-----|

|                                  |     |
|----------------------------------|-----|
| <b>Package Quantity (Metric)</b> | 500 |
|----------------------------------|-----|

|                       |            |
|-----------------------|------------|
| <b>Customs Number</b> | 3926909987 |
|-----------------------|------------|

